KHS Innocoll DP 1523





^{*}example illustration

adhesives for labeling

- ✓ based on dispersion
- for PET / PEN
- for critical plastic surfaces
- for paper labels
- easily removable in washmachine
- raw materials correspond to the FDA Directives 21 CFR 175. 105.

product characteristics

The adhesive is suitable for labelling critical plastic surfaces (e.g. PET) in the beverage industry and has a good resistance to condensate water.

application notes

The temperature processing range is 20 - 30 °C, ideal at approx. 27 °C. Before a different adhesive is to be used on the machine, it must be carefully cleaned.

storage

The product can be stored in its original sealed container for at least 6 months at room temperature after date of production - but not below +4 °C.

characteristics	Innocoll DP 1523
viscosity, dyn.	50.000 ± 10.000 mPas
colour	light beige
pH value	8,0 ± 0,2
density	1,02 ± 0,03 g/cm3

container	packing size	material number
33 kg	18	301244607100
1000 kg	1	301244607101
120 kg	4	301244607102
30 kg	18	301244607110

To the best of our knowledge and experience, the data / information we have provided is reliable but it does not amount to a statement of assured properties in the context of the latest regulations issued by the Federal Court of Justice. With regard to the many options available in terms of alternative applications and operating conditions the data / information can only be regarded as of a non-binding nature. In each separate case it is necessary for you to carry out your own trials before large-scale use although, of course, in that respect our application technology is available to you upon request.