KHS Innocoll HMP E 5441









^{*}example illustration

hot melts for packaging

- synthetic resins
- multi-purpose packaging adhesive
- for difficult substrates
- good hot tack
- low consumption
- odour and smoke free

product characteristics

The product is a multi-purpose packaging adhesive that is used in a wide range of packaging applications, such as carton sealing, tray erection, ream wrapping and assembly of difficult substrates. It has a good hot tack, low consumption and it is odour and smoke free.

application notes

For use in nozzle, roller or other application systems. During extended machine stops it is recommended to switch off the heating. Temperatures above 190 °C should be avoided.

storage

Cool and dry at least 12 months storable. Use old stock first.

characteristics	Innocoll HMP E 5441
viscosity, dyn.	ca. 1800 mPas (Brookfield Thermosel 160°C)
colour	slightly yellowish
open time	middle
Softening Point (R&B)	110 ± 5 °C

conta	ainer	packing size	material number
20	kg	30	301244605120

To the best of our knowledge and experience, the data / information we have provided is reliable but it does not amount to a statement of assured properties in the context of the latest regulations issued by the Federal Court of Justice. With regard to the many options available in terms of alternative applications and operating conditions the data / information can only be regarded as of a non-binding nature. In each separate case it is necessary for you to carry out your own trials before large-scale use although, of course, in that respect our application technology is available to you upon request.